



The most cost-effective outdoor spot light with better efficient and performance

UniPoint

Our UniPoint is designed to produce both general and accent lighting while concealing the body of the device, allowing only the light to be exposed. This design can be used to change the surroundings by adding subtle or dramatic contrasting effects. It also includes exclusive features such as energy efficiency, chromatic quality and miniaturization. We guarantee extreme reliability and high level of resistance to adverse weather conditions and vandalism

Benefits

- In stylish and very compact design
- Price point versus PHILIPS standards
- Effortless and flexible installation
- Customizing for you

Features

- High quality LED
- Different choice of light source and beam angles
- Die-cast aluminum housing + dark grey sand coating to ensure anticorrosion
- Structural waterproof technology
- IP66
- IK06
- Quality and reliability in line with all regulations

Application

- Buildings
- Statues
- Columns
- Pillars
- Eaves

Versions



UniPoint BGP312 3LED



UniPoint BGP312 5LED

Accessories



ZGP312 1&3LED Mounting Clip
Photo

Ordercode 01711742



ZGP312 5LED Mounting Clip
Dimensional Drawing

Ordercode 01711752

Approval and Application

Mech. impact protection code IK06

Controls and Dimming

Dimmable No

General Information

CE mark -
 Optical cover/lens type GB
 Driver included No
 Light source replaceable No

Initial Performance (IEC Compliant)

Init. Color Rendering Index >75

Light Technical

Standard tilt angle side entry -
 Standard tilt angle posttop -

Mechanical and Housing

Color Dark gray

General Information

Order Code	Full Product Name	Luminaire light beam	
		spread	Light source color Optic type
01710762	BGP312 3LED 3000K NB	10°	830 warm white Narrow beam angle 10°
01710852	BGP312 5LED 3000K NB	10°	830 warm white Narrow beam angle 10°
01710902	BGP312 5LED 4000K WB	40°	840 neutral white Wide beam angle 42°

Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Color	
		Temperature	Initial luminous flux
01710762	BGP312 3LED 3000K NB	3000 K	330 lm
01710852	BGP312 5LED 3000K NB	3000 K	595 lm

Order Code	Full Product Name	Init. Corr. Color	
		Temperature	Initial luminous flux
01710902	BGP312 5LED 4000K WB	4000 K	595 lm

