



# UniStreet gen2

## BGP281 LED20-4S/740 I DN10 SRG10 48/60S

UNISTREET GEN2 MICRO - LED Module 2000 lm - 740 neutral white - Safety class I (I) - Distribution narrow 10 - Side-entry for diameter 48-60 mm

Designed for large-scale ledification projects, the UniStreet gen2 is the ideal 1:1 luminaire replacement for municipalities. Thanks to its high efficiency and low initial cost, the UniStreet gen2 luminaire enables a fast payback and significant savings in terms of energy consumption within a short period of time. The ease of installation and maintenance is enabled by the Philips Service tag and the Philips SR (System Ready) socket makes it future-ready and you can pair this luminaire with lighting control and software applications such as Interact City. Available with a number of different optics and lumen packages that can even be tuned further to fit exact project requirements, UniStreet gen2 is a true point-to-point replacement solution for conventional light sources. The compact luminaire, using high-quality materials is also easy to dismantle and recycle at the end of its lifetime.

### Product data

General information			
Lamp family code	LED20 [ LED Module 2000 lm]	Cable	-
Light source color	740 neutral white	Protection class IEC	Safety class I (I)
Light source replaceable	Yes	Flammability mark	F [ For mounting on normally flammable surfaces]
Number of gear units	1 unit	CE mark	CE mark
Driver/power unit/transformer	PSR [ Power supply unit regulating]	ENEC mark	ENEC plus mark
Driver included	Yes	Warranty period	5 years
Optical cover/lens type	FG [ Flat glass]	Optic type outdoor	Distribution narrow 10
Luminaire light beam spread	68° x 158°	Remarks	* At extreme ambient temperatures the luminaire might automatically dim down to protect components
Control interface	-		
Connection	2 Push-in connector 5-pole		

# UniStreet gen2

Constant light output	No
Number of products on MCB of 16 A type B	29
EU RoHS compliant	Yes
Light source engine type	LED
Service tag	Yes
Serviceability class	Class A, luminaire is equipped with serviceable parts (when applicable): LED board, driver, control units, surge protection device, optics, front cover and mechanical parts
Product family code	BGP281 [ UNISTREET GEN2 MICRO]

## Light technical

Upward light output ratio	0
Standard tilt angle posttop	0°
Standard tilt angle side entry	0°

## Operating and electrical

Input Voltage	220 to 240 V
Input Frequency	50 to 60 Hz
Inrush current	15 A
Inrush time	0.295 ms
Power Factor (Min)	0.98

## Controls and dimming

Dimmable	No
----------	----

## Mechanical and housing

Housing Material	Aluminum die-cast
Reflector material	Polycarbonate
Optic material	Polymethyl methacrylate
Optical cover/lens material	Glass
Fixation material	Aluminum
Mounting device	48/60S [ Side-entry for diameter 48-60 mm]
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	520 mm
Overall width	234 mm
Overall height	95 mm
Effective projected area	0.0235 m <sup>2</sup>
Color	Gray

Dimensions (Height x Width x Depth)	95 x 234 x 520 mm (3.7 x 9.2 x 20.5 in)
-------------------------------------	---

## Approval and application

Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [ 5 J vandal-protected]
Surge Protection (Common/Differential)	Surge protection level until 10 kV

## Initial performance (IEC compliant)

Initial luminous flux (system flux)	1780 lm
Luminous flux tolerance	+/-7%
Initial LED luminaire efficacy	129 lm/W
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	70
Initial chromaticity	(0.381, 0.379) SDCM <5
Initial input power	13.8 W
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

## Over time performance (IEC compliant)

Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* L96 100000 h	

## Application conditions

Ambient temperature range	-40 to +50 °C
Performance ambient temperature Tq	25 °C
Maximum dim level	0% (digital)


## Product data

Full product code	871951407978600
Order product name	BGP281 LED20-4S/740 I DN10 SRG10 48/60S
EAN/UPC - Product	8719514079786
Order code	07978600
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910925866713
Net Weight (Piece)	4.100 kg



# UniStreet gen2

## Dimensional drawing



BGP281 LED20-4S/740 | DN10 SRG10 48/60S

