



MASTER TL-D Xtreme

MASTER TL-D Xtreme 36W/830 1SL/25

Low-pressure mercury discharge lamp with a tubular 26mm envelope

Warnings and Safety

- To achieve published lifetimes for 100% operation, do not dim below 30%
- When used on electromagnetic gear, it is strongly recommended to apply only Philips S10 or S10E starters (for 18W types S2 or S2E) to achieve the published lifetimes, and to install new starters when relamping.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information		Operating and Electrical	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Luminous Efficacy (rated) (Nom)	90 lm/W
Life to 50% Failures (Nom)	47000 h	Colour Rendering Index horiz (Nom)	>80
Life to 50% Failures Preheat (Nom)	79000 h	Depreciation 2000 hrs	96 %
LSF 2000 h Rated	100 %	LLMF 4000 h Rated	95 %
LSF 4000 h Rated	99 %	Depreciation 5000 hrs	94 %
LSF 6000 h Rated	99 %	LLMF 8000 h Rated	93 %
LSF 8000 h Rated	99 %	LLMF 12000 h Rated	92 %
LSF 12000 h Rated	99 %	LLMF 16000 h Rated	91 %
LSF 16000 h Rated	99 %	LLMF 20000 h Rated	90 %
LSF 20000 h Rated	99 %		
Light Technical		Temperature	
Colour Code	830 [CCT of 3000K]	Design Temperature (Nom)	25 °C
Luminous Flux (Nom)	3250 lm		
Luminous Flux (Rated) (Nom)	3250 lm		
Colour Designation	Warm White (WW)		
Colour Temperature, horizontal (Nom)	3000 K		

MASTER TL-D Xtreme

Controls and Dimming

Dimmable	Yes
----------	-----

Approval and Application

Energy Efficiency Label	A
Mercury (Hg) Content (Nom)	3.0 mg
Energy Consumption kWh/1000 h	42 kWh

Product Data

Full product code	871150055866440
-------------------	-----------------



Order product name	MASTER TL-D Xtreme 36W/830 SLV
EAN/UPC - Product	8711500558664
Order code	55866440
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	25
Material Nr. (12NC)	927982383014
Net Weight (Piece)	135.000 g
ILCOS Code	FD-36/30/1B-E-G13

Dimensional drawing

Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Xtreme 36W/830 SLV	28 mm	1199.4 mm	1206.5 mm	1204.1 mm	1213.6 mm

TL-D Xtreme 36W/830

Photometric data




Lightcolour /830

Lightcolour /830



MASTER TL-D Xtreme

Lifetime



LDLE_TL-D8LL_0001-Life expectancy diagram

LDLE_TL-D8LL_0002-Life expectancy diagram



LDLE_TL-D8LL_0003-Life expectancy diagram

LDLM_TL-D8LL_0001-Lumen maintenance diagram

