



MASTER TL5 High Output Eco

MASTER TL5 HO Eco 73=80W/830 UNP/40

This extremely efficient TL5 lamp (tube diameter 16 mm) saves considerable energy by simple lamp-for-lamp replacement. The TL5 HO Eco lamp is optimized for installations requiring high light output and offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

Warnings and Safety

- A reduction in energy consumption is only achieved with current-controlled gear.
- The lamps operate perfectly with power-controlled gear, but in that case the light output can be up to 10% higher.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	G5 [G5]
Life to 50% Failures Preheat (Nom)	30000 h
Features	na [Not Applicable]
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	99 %
LSF Preheat 6000 h Rated	99 %
LSF Preheat 8000 h Rated	99 %
LSF Preheat 16000 h Rated	99 %
LSF Preheat 20000 h Rated	94 %
Light Technical	
Colour Code	830 [CCT of 3000K]

Luminous Flux (Nom)	7000 lm
Luminous Flux (Rated) (Nom)	6550 lm
Colour Designation	Warm White (WW)
Luminous Efficacy (@ Max Lumen, Rated) (Nom)	95 lm/W
Colour Temperature, horizontal (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	89 lm/W
Colour Rendering Index horiz (Max)	85
Colour Rendering Index horiz (Min)	80
Colour Rendering Index horiz (Nom)	82
Depreciation 2000 hrs	96 %
LLMF 4000 h Rated	95 %
Depreciation 5000 hrs	94 %

MASTER TL5 High Output Eco

LLMF 8000 h Rated	93 %
LLMF 12000 h Rated	92 %
LLMF 16000 h Rated	91 %
LLMF 20000 h Rated	90 %

Operating and Electrical

Power (Rated) (Nom)	73.3 W
Lamp Current (Nom)	0.550 A

Temperature

Design Temperature (Nom)	35 °C
--------------------------	-------

Controls and Dimming

Dimmable	Yes
----------	-----

Approval and Application

Energy Efficiency Label	A+
-------------------------	----

Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	80 kWh

Product Data


Full product code	872790082596100
Order product name	MASTER TL5 HO Eco 73=80W/830 UNP/40
EAN/UPC - Product	8711500880086
Order code	82596100
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	40
Material Nr. (12NC)	927991883031
Net Weight (Piece)	128.700 g
ILCOS Code	FDH-73/30/1B-L/P-G5-16/1450

Dimensional drawing


Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HO Eco 73=80W/830 UNP/40	17 mm	1449.0 mm	1456.1 mm	1453.7 mm	1463.2 mm

TL5 HO Eco 73=80W/830

Photometric data



Lightcolour /830



Lightcolour /830


MASTER TL5 High Output Eco

Lifetime



LDLE_TL5ECO_0001-Life expectancy diagram

LDLE_TL5ECO_0002-Life expectancy diagram



LDLM_TL5ECO_0001-Lumen maintenance diagram

