



MASTER TL-E Circular Super 80

TL-E 32W/865 1CT/12

Low-pressure mercury discharge lamps with a circular 26 mm tube

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	G10Q [G10q]
Life to 50% Failures (Nom)	13000 h
LSF 2000 h Rated	98 %
LSF 4000 h Rated	77 %
LSF 6000 h Rated	60 %
LSF 8000 h Rated	45 %
Light Technical	
Colour Code	865 [CCT of 6500K]
Luminous Flux (Nom)	2310 lm
Luminous Flux (Rated) (Nom)	2310 lm
Colour Designation	Cool Daylight
Colour Temperature, horizontal (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	72 lm/W
Colour Rendering Index horiz (Nom)	80
Depreciation 2000 hrs	84 %
LLMF 4000 h Rated	79 %
Depreciation 5000 hrs	75 %

LLMF 8000 h Rated	73 %
Operating and Electrical	
Power (Rated) (Nom)	32.0 W
Lamp Current (Nom)	0.450 A
Voltage (Nom)	81 V
Temperature	
Design Temperature (Nom)	25 °C
Controls and Dimming	
Dimmable	Yes
Approval and Application	
Energy Efficiency Label	A
Mercury (Hg) Content (Nom)	8 mg
Energy Consumption kWh/1000 h	35 kWh


MASTER TL-E Circular Super 80

Product Data

Full product code	872790084055100
Order product name	TL-E 32W/865 1CT/12
EAN/UPC - Product	8727900840551
Order code	84055100
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	12
Material Nr. (12NC)	928026386570
Net Weight (Piece)	0.180 kg
ILCOS Code	FSC-32/65/1B-E-G10q-29/299

Dimensional drawing



TL-E 32W/865

Product	D (max)	D (min)	E (min)	E (max)	I (min)	I (max)
TL-E 32W/865 1CT/12	30.9 mm	27.1 mm	299.0 mm	303.5 mm	241.0 mm	246.0 mm

