

**PHILIPS**

Lighting



# MASTER TL-E Circular Super 80



## TL-E 40W/865 1CT/12

Low-pressure mercury discharge lamps with a circular 26 mm tube

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General information	
Cap-Base	G10Q [ G10q]
Life to 50% Failures (Nom)	13000 h
LSF 2000 h Rated	98 %
LSF 4000 h Rated	77 %
LSF 6000 h Rated	60 %
LSF 8000 h Rated	45 %
Flux measurement reference	Sphere
Light technical	
Colour Code	865 [ CCT of 6500K]
Luminous Flux (Nom)	3070 lm
Luminous Flux (Rated) (Nom)	3070 lm
Colour Designation	Cool Daylight
Chromaticity Coordinate X (Nom)	0.313
Chromaticity Coordinate Y (Nom)	0.337
Colour Temperature, horizontal (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	78 lm/W
Colour Rendering Index horiz (Nom)	80

Depreciation 2000 hrs	89 %
LLMF 4000 h Rated	84 %
Depreciation 5000 hrs	81 %
LLMF 8000 h Rated	80 %
Operating and electrical	
Power (Rated) (Nom)	40.8 W
Lamp Current (Nom)	0.420 A
Voltage (Nom)	110 V
Temperature	
Design Temperature (Nom)	25 °C
Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Bulb Shape	C-T9 [ C-T 29 mm (C-T9)]

# MASTER TL-E Circular Super 80

## Approval and application


Energy Efficiency Class	G
Mercury (Hg) Content (Max)	8 mg
Mercury (Hg) Content (Nom)	8 mg
Energy Consumption kWh/1000 h	41 kWh
EPREL Registration Number	423513

## Product data

Full product code	872790084057500
Order product name	TL-E 40W/865 1CT/12

EAN/UPC - Product	8727900840575
Order code	84057500
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928027486570
Net Weight (Piece)	0.250 kg
ILCOS Code	FSC-40/65/1B-E-G10q-29/400

## Dimensional drawing



TL-E 40W/865 1CT/12

Product	D (max)	D (min)	E (min)	E (max)	I (min)	I (max)
TL-E 40W/865 1CT/12	30.9 mm	27.1 mm	393.7 mm	406.4 mm	341.0 mm	347.7 mm

