



TL-M Rapid Start Standard Colours

TL-M RS 65W/33-640 1SL/25

Low-pressure mercury discharge lamps with a tubular 38 mm envelope

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


Product data

General Information		Voltage (Nom)	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	110 V	
Life to 50% Failures (Nom)	13000 h	Controls and Dimming	
System Description	Rapid Start (RS)	Dimmable	Yes
Light Technical		Approval and Application	
Colour Code	33-640	Energy Efficiency Label	A
Luminous Flux (Nom)	4750 lm	Mercury (Hg) Content (Nom)	8.0 mg
Colour Designation	Cool White (CW)	Energy Consumption kWh/1000 h	74 kWh
Lumen Maintenance 10000 h (Nom)	73 %	Product Data	
Lumen Maintenance 2000 h (Nom)	90 %	Full product code	871150072486140
Lumen Maintenance 5000 h (Nom)	81 %	Order product name	TL-M RS 65W/33-640 1SL/25
Colour Temperature, horizontal (Nom)	4100 K	EAN/UPC - Product	8711500724861
Luminous Efficacy (rated) (Nom)	74 lm/W	Order code	72486140
Colour Rendering Index horiz (Nom)	63	Numerator - Quantity Per Pack	1
Operating and Electrical		Numerator - Packs per outer box	25
Power (Rated) (Nom)	64.0 W	Material Nr. (12NC)	928031003371
Lamp Current (Nom)	0.670 A	Net Weight (Piece)	344.200 g

TL-M Rapid Start Standard Colours

ILCOS Code FD-65/41/2B-LC/P-G13



Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TL-M RS 65W/33-640 1SL/25	40.5 mm	1500 mm	1507.1 mm	1504.7 mm	1514.2 mm

TL-M 65W/33-640 RS

Photometric data



Lightcolour /33-640

Lightcolour /33-640

