



# CorePro LED tube Universal T8



## CorePro LEDtube UN 1500mm HO 23W865 T8

The new Philips CorePro LEDtube Universal T8 brings simplicity to your lighting project. You don't need to pay attention to the driver technology anymore. Thanks to a unique design, Philips CorePro LEDtube Universal T8 directly fits in luminaires operating either on Electro Magnetic ballasts or HF Electronic ballasts or mains power connection. So simple to operate and no need to carry double stock of products! Perfectly safe, reliable & easy to install Philips CorePro LEDtube Universal T8 is the ideal alternative to standard fluorescent tubes to save energy and lower investment.

### Product data

General Information	
Cap-Base	G13 [ Medium Bi-Pin Fluorescent]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	30000 h
Switching Cycle	50000X
Flux measurement reference	Sphere

Light Technical	
Colour Code	865 [ CCT of 6500K]
Beam Angle (Nom)	240 °
Luminous Flux (Nom)	2700 lm
Colour Designation	Cool Daylight
Colour Temperature, horizontal (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	117.00 lm/W
Color Consistency	<6
Colour Rendering Index horiz (Nom)	80

LLMF At End Of Nominal Lifetime (Nom) 70 %	
--	--

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	23 W
Lamp Current (Nom)	130 mA
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.9
Voltage (Nom)	220-240 V


Temperature	
T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C

# CorePro LED tube Universal T8

T-Case Maximum (Nom)	60 °C
<b>Controls and Dimming</b>	
Dimmable	No
<b>Mechanical and Housing</b>	
Bulb Finish	Frosted
Bulb Material	Glass
Product Length	1500 mm
Bulb Shape	Tube, double-ended
<b>Approval and Application</b>	
Energy Efficiency Class	E
Energy Saving Product	Yes
Approval Marks	RoHS compliance TUV CE marking KEMA Keur certificate

Energy Consumption kWh/1000 h	23 kWh
EPREL Registration Number	403585
<b>Product Data</b>	
Full product code	871869680176500
Order product name	CorePro LEDtube UN 1500mm HO 23W865 T8
EAN/UPC - Product	8718696801765
Order code	80176500
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001869702
Net Weight (Piece)	0.270 kg


## Dimensional drawing




TLED 1500mm UNV24W-54W 3100lm 6500K

Product	D1	D2	A1	A2	A3
CorePro LEDtube UN 1500mm HO 23W865 T8	27.9 mm	28 mm	1500 mm	1505.9 mm	1514.2 mm

## Photometric data




23W G13 865 6500K



18W G13 830 3000K



# CorePro LED tube Universal T8

## Photometric data





18W G13

## Lifetime



LEDtube COR SLR 23W 30K FailureRate-LED-LED

LEDtube COR SLR 23W 30K LumenVsTc-LMP-LMP




18W G13

18W G13

# CorePro LED tube Universal T8

## Lifetime



LEDtube COR SLR 23W 30K LifetimeVsTc-LED-LED

