



Tornado High Lumen

Tornado High Lumen 75W CDL E40 1CT/6

Energy saving lamp in spiral shape, with superior performance (long life, high switching) and high lumen warm bright light. Perfectly suitable to be used in places where high lumen is required, and the lamp is directly visible.

Warnings and Safety

- Breaking a lamp is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a closed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- Compact fluorescent lamps have to be treated as special waste, they must be taken to your local waste facilities for recycling. The European Lighting Industry has set up an infrastructure, capable of recycling mercury, other metals, glass etc.

Product data

General Information		LLMF At End Of Nominal Lifetime (Nom)	
Cap-Base	E40 [E40]	60 %	
Nominal Lifetime (Nom)	10000 h	Operating and Electrical	
Switching Cycle	10000X	Input Frequency	50 or 60 Hz
Light Technical		Power (Rated) (Nom)	75.0 W
Colour Code	865 [CCT of 6500K]	Lamp Current (Nom)	350 mA
Luminous Flux (Nom)	5550 lm	Starting Time (Nom)	1.5 s
Luminous Flux (Rated) (Nom)	5550 lm	Warm Up Time to 60% Light (Max)	60 s
Colour Designation	Cool Daylight	Power Factor (Nom)	0.92
Lumen Maintenance 2000 h (Nom)	88 %	Voltage (Nom)	220-240 V
Chromaticity Coordinate X (Nom)	313	Controls and Dimming	
Chromaticity Coordinate Y (Nom)	337	Dimmable	No
Colour Temperature, horizontal (Nom)	6500 K	Approval and Application	
Luminous Efficacy (rated) (Nom)	73.96 lm/W	Energy Efficiency Label	A
Colour Rendering Index horiz (Nom)	80	Mercury (Hg) Content (Max)	5 mg

Tornado High Lumen

Energy Consumption kWh/1000 h	75 kWh
Product Data	
Full product code	872790080723300
Order product name	Tornado High Lumen 75W CDL E40 1CT/6
EAN/UPC - Product	8727900807233
Order code	80723300

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929676006501
Net Weight (Piece)	0.360 kg

Dimensional drawing



Product	C (max)	F (max)	D (max)
Tornado High Lumen 75W CDL E40 1CT/6	293 mm	88.1 mm	102 mm

HL HS HV 10Kh EMI HPF 80W 220-240VE40CDL

