



Capsules LV 3000 h

Caps 3000h 14.3W GY6.35 12V 1CT/10x10F

Low-voltage halogen capsule. Ideal solution for small decorative luminaires. UV-block glass and low-pressure filling allow usage without cover glass. The compact halogen capsule delivers crisp white light over a long lifetime.


Product data

General information	
Cap-Base	GY6.35 [GY6.35]
Operating Position	UNIVERSAL [Any or Universal (U)]
Nominal Lifetime (Nom)	3000 h
Switching Cycle	12000X
Rated Lifetime (Hours)	3000 h
Light technical	
Luminous Flux (Nom)	232 lm
Luminous Flux (Rated) (Nom)	232 lm
Colour Temperature, horizontal (Nom)	2900 K
Luminous Efficacy (rated) (Nom)	16.6 lm/W
Colour Rendering Index horiz (Nom)	100
Operating and electrical	
Power (Rated) (Nom)	14.0 W
Lamp Current (Nom)	1.167 A
Starting Time (Nom)	0.0 s
Warm Up Time to 60% Light (Nom)	Instant full light s
Power Factor (Nom)	1
Voltage (Nom)	12 V
Controls and dimming	
Dimmable	Yes

Mechanical and housing	
Bulb Finish	Clear
Bulb Shape	T11 [T 11mm]
Approval and application	
Energy Consumption kWh/1000 h	14 kWh
Luminaire design requirements	
Bulb Temperature (Max)	600 °C
Pinch Temperature (Max)	350 °C
Pinch Temperature (Max)-DUP(do not use)	350 °C
Product data	
Full product code	87186968277200
Order product name	Caps 3000h 14.3W GY6.35 12V 1CT/10x10F
EAN/UPC - Product	8718696827772
Order code	82777200
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	100
Material Nr. (12NC)	925723517104
Net Weight (Piece)	0.003 kg

Capsules LV 3000 h

Dimensional drawing



Product	D (max)	L	C (max)
Caps 3000h 14.3W GY6.35 12V 1CT/10x10F	12 mm	30 mm	44 mm

Caps 3000h 14.3W GY6.35 12V 1CT/10x10F

