



# Maxos accessories

## 9MX056 CBA BK

### Chain bracket adjustable

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

### Product data

General Information	
Protection class IEC	-
Suspension accessories	CBA [ Chain bracket adjustable]
Mechanical accessories	No [-]
Packaging configuration	No [-]
Accessory color	Black
Emergency lighting accessories	No [-]
Product family code	9MX056 [ ACC MAXOS]
Light Technical	
Optical cover/lens type accessory	No [-]
Operating and Electrical	
Electrical accessories	No [-]

Circuit	No [-]
Mechanical and Housing	
Length	- mm
Dimensions (Height x Width x Depth)	NaN x NaN x NaN mm (NaN x NaN x NaN in)
Approval and Application	
Ingress protection code	- [-]
Product Data	
Full product code	403073225202200
Order product name	9MX056 CBA BK
EAN/UPC - Product	4030732252022
Order code	25202200

## Maxos accessories

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material Nr. (12NC)	910629113626

Net Weight (Piece)	0,115 kg
--------------------	----------

