



HF-Performer II for PL-T/C/R/L/TL5C lamps

HF-P 2 22-42 PL-T/C/L/TL5C EII 220-240V

Compact, lightweight high-frequency electronic ballast for PL-T/C/TL5C/R/L fluorescent lamps, based on EII technology

Product data

General Information			
Application Code	EII	Mains Voltage Safety (AC)	-10%~+10%
Type Version	mk4	Earth Leakage Current (Nom)	0.5 mA
Lamp Type	PL-T/C/L/TL5C	Inrush Current Width	0.35 ms
Number of Lamps	2 piece/unit	Constant Wattage Deviation	-2%/+2%
Number of Products on MCB (16A Type B) (Nom)	12	Ballast Factor (Nom)	1
Automatic Restart	Yes	Power Losses (Nom)	4.35-4.93 W
		Inrush Current Peak (Max)	31 A
Operating and Electrical		Wiring	
Input Voltage	220 to 240 V	Connector Type Input Terminals	Insert
Input Frequency	50 to 60 Hz	Cable Capacity Output Wires Mutual (Nom)	100 pF
Operating Frequency (Max)	- kHz	Connector Type Output Terminals	Insert
Operating Frequency (Min)	42 kHz	Cable Length Hot Wiring	0.75 m
Operating Frequency (Nom)	45 kHz	Wire Striplength	7.5-8.5 mm
Ignition Method	Warm Start	Dual Fixture Master/Slave	Not applicable [Master/Slave oper. not applicable]
Crestfactor (Max)	1.7	Input Terminal Cross Section	0.50-1.50 mm ²
Power Factor 100% Load (Nom)	0.95	Output Terminal Cross Section	0.50-1.50 mm ²
Ignition Time (Max)	0.52 s	Cable Capacity Output Wires to Earth (Nom)	100 pF
Mains Voltage Performance (AC)	-8%~+6%		

HF-Performer II for PL-T/C/R/L/TL5C lamps

System characteristics	
Rated Ballast-Lamp Power	22-42 W
Rated Lamp Power on PL-T/C	22/42 W
Temperature	
T-Ambient (Max)	50 °C
T-Ambient (Min)	-25 °C
T-Storage (Max)	80 °C
T-Storage (Min)	-40 °C
T-Case Lifetime (Nom)	75 °C
T-Case Maximum (Max)	75 °C
T-Ignition (Max)	50 °C
T-Ignition (Min)	-25 °C
Emergency Operation	
Battery Voltage Lamp Ignition	198-254 V
Battery Voltage Lamp Operation	176-254
Approval and Application	
Energy Efficiency Index	A2
IP Classification	IP 20 [Ingress Protection 20]
EMI 9 kHz ... 30 MHz	EN55015
EMI 30 MHz ... 1000 MHz	EN55022 level B
Safety Standard	IEC 61347-2-3
Performance Standard	IEC 60929

Quality Standard	ISO 9000:2000
Environmental Standard	ISO 14001
Harmonic Current Emission Standard	IEC 61000-3-2
EMC Immunity Standard	IEC 61547
Vibration Standard	IEC68-2-6 F c
Bumps Standard	IEC 68-2-29 Eb
Humidity Standard	EN 61347-2-3 clause 11
Approval Marks	CE marking ENEC certificate VDE-EMV certificate
Temperature Marking	Yes
Emergency Standard	IEC 60598-2-22
Hum And Noise Level	Inaudible

Product Data	
Full product code	871150091399930
Order product name	HF-P 2 22-42 PL-T/C/L/TL5C EII 220-240V
EAN/UPC - Product	8711500913999
Order code	91399930
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	913700630866
Net Weight (Piece)	0.150 kg

Dimensional drawing

Product	D1	C1	A1	A2	B1	B2
HF-P 2 22-42 PL-T/C/L/	4.5 mm	30.0	103.0	93.5	67.0	57.5
TL5C EII 220-240V		mm	mm	mm	mm	mm

HF-P 2 22-42 PL-T/C/L/TL5C EII 220-240V

HF-Performer II for PL-T/C/R/L/TL5C lamps

