

Master Value LEDtube T8

MASTER LEDtube VLE 600mm HO 8W 830 T8

A high performance LED solution, the professional Master Value LED tube is ideal for replacing T8 fluorescent lamps using EM ballast or installing directly on the mains. This product provides a uniform lighting effect for use in all general lighting, as well as instant energy efficiency, making for an environmentally friendly solution.

Product data


General Information		Lamp Current (Max)	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]	Lamp Current (Max)	38 mA
EU RoHS compliant	Yes	Lamp Current (Min)	34 mA
Nominal Lifetime (Nom)	50000 h	Starting Time (Nom)	0.5 s
Switching Cycle	200000X	Warm Up Time to 60% Light (Nom)	0.5 s
Light Technical		Power Factor (Nom)	0.9
Colour Code	830 [CCT of 3000K]	Voltage (Nom)	220-240 V
Beam Angle (Nom)	240 °	Temperature	
Luminous Flux (Nom)	1000 lm	T-Ambient (Max)	45 °C
Colour Designation	White (WH)	T-Ambient (Min)	-20 °C
Colour Temperature, horizontal (Nom)	3000 K	T-Storage (Max)	65 °C
Luminous Efficacy (rated) (Nom)	125.00 lm/W	T-Storage (Min)	-40 °C
Color Consistency	<6	T-Case Maximum (Nom)	50 °C
Colour Rendering Index horiz (Nom)	83	Controls and Dimming	
LLMF At End Of Nominal Lifetime (Nom)	70 %	Dimmable	No
Operating and Electrical		Mechanical and Housing	
Input Frequency	50 to 60 Hz	Bulb Material	Glass
Power (Rated) (Nom)	8 W		

Master Value LEDtube T8

Product Length	600 mm
Approval and Application	
Energy Efficiency Label	A++
Energy Saving Product	Yes
Approval Marks	RoHS compliance TUV CE marking KEMA Keur certificate
Energy Consumption kWh/1000 h	8 kWh
Product Data	
Full product code	871869964679000

Order product name	MASTER LEDtube VLE 600mm HO 8W 830 T8
EAN/UPC - Product	8718699646790
Order code	64679000
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002021102
Net Weight (Piece)	0.120 kg



Dimensional drawing



Product	D1	D2	A1	A2	A3
MASTER LEDtube VLE 600mm HO 8W 830 T8	25.8 mm	28 mm	588.5 mm	595.5 mm	602.5 mm

TLED 2ft 220-240V 8-18W 1000lm 3000K G13

Photometric data



LEDtube 220-240V G13 2ft 1000lm 3000k

LEDtube 220-240V G13


Master Value LEDtube T8

Photometric data




LEDtube 220-240V G13 3000k


Lifetime




LEDtube 220-240V G13



LEDtube 220-240V G13




LEDtube 220-240V G13 LifetimeVsTc



LEDtube 220-240V G13 2ft LumenVsTc

Master Value LEDtube T8

Lifetime



LEDtube 220-240V G13 FailureRate

